

# A Comparative Study of PAPR Reduction Techniques in OFDM

Monika Sahu#1, Prateek Nigam \*2, Dr. Vijayshri Chaurasia#3

# M.Tech Scholar –Asst. Professor, RGTU – MANIT, BHOPAL

RKDFIST Bhopal -India

1 sahumonica88@gmail.com

\* Prateek Nigam

Phd Scholar AISECT University Bhopal-India

2 er.nigam@gmail.com

**Abstract**—Orthogonal Frequency division multiplexing is well known technique to combat the multipath fading effect for radio waves. However, OFDM faces the Peak to Average Power Ratio (PAPR) problem that is a main disadvantage in OFDM, which reduces the efficiency of the transmit signal in RF section of the transmitter.

This paper present Reduction of PAPR using all proposed techniques. These techniques give better results for PAPR Reduction. Any technique can be used according to the need of parameter performance.

**Keywords**— Orthogonal Frequency Division Multiplexing (OFDM), Peak-to-Average Power Ratio (PAPR)

## I. INTRODUCTION

Orthogonal frequency division multiplexing (OFDM) is a efficient technology for multipath transmission. It is the attractive multiplexing technique for fourth generation (4G) wireless system. It offers the solution of multipath fading channel and improvement in bandwidth efficiency but it would lead to inefficient amplification (i.e. large input power required). One of the problems in OFDM is PAPR (Peak to average power ratio). For efficient signal transmission this PAPR should be reduce [1]. Different PAPR reduction technique can be use in OFDM system. In this paper describe different PAPR reduction techniques in OFDM system All the reducing techniques has the advantage in terms of their own parameter performance. This paper contain an overview of all PAPR reduction techniques in OFDM system This paper organized as follow: First we describe the OFDM and their application, in section II. And then we calculate or investigate the PAPR in OFDM system in section III. Then after we describe the proposed PAPR reduction techniques in section IV, and finally we present some conclusion in section V.

## II. PAGE LAYOUT

OFDM is multicarrier transmission technique used for many wireless communication standards Such as Digital Television Broadcasting (DTB), where

$$\frac{1}{NT} \cdot \int_0^{NT} |x(t)|^2 dt$$

is the average value of x(t).

Mobile world-wide interoperability for microwave access (Mobile Wimax), Digital audio broadcasting (DAB) and 3GPP long term evolution (LTE)[2]. International standards used for OFDM In

high speed wireless communication are already established by IEEE 802.11, IEEE 802.20, and broadcast radio Access network committees.

The Basic principle of OFDM is to split a high data rate steam into a number of lower rate steams which are transmitted simultaneously over subcarrier. It eliminates the need for equalizers; the efficient technique can be realized by Fast Fourier transform (FFT) technique. The OFDM uses the spectrum more efficiently by making the entire sub carrier orthogonal to one another, preventing interference between the sub carriers.

## 3. PAPR PROBLEM & REDUCTION

In OFDM information is carried on several orthogonal subcarriers. Each subcarrier being mapped by a complex constellation like QAM or PSK. If we consider N bit  $X_k = (X_0, X_1, \dots, X_{N-1})$ , over a time  $[0, T]$ , the OFDM signal can be express as

$$x(t) = \sum_{k=0}^{N-1} X_k e^{j2\pi k f_0 t} \quad (1)$$

Where:  $f_0 = 1/T$  By putting  $t = nT_b$ , where  $T_b = T/N$ , we arrive at the discrete time domain given by

$$x_n = \sum_{k=0}^{N-1} X_k e^{j2\pi kn/N} \quad (2)$$

The PAPR of the signal x(t) is the ratio of the peak instantaneous power to the average power, can be **express as**

$$\text{PAPR} = \frac{\max_{0 \leq t < NT} |x(t)|^2}{\frac{1}{NT} \cdot \int_0^{NT} |x(t)|^2 dt}$$

If  $N$  is large enough the  $x(t)$  has real and imaginary part follow Gaussian distribution and its envelope will follow a Rayleigh distribution. Due to central limit theorem this large value of  $N$  results large PAPR.

#### 4. PAPR REDUCTION TECHNIQUE

Various PAPR reduction techniques have been proposed past decade. These techniques are divided into two parts first is the scrambling techniques and another is signal distortion techniques.

##### 4.1 SIGNAL SCRAMBLING TECHNIQUES

Block coding technique [1], Selected mapping (SLM)[3], Partial transmit sequence (PTS)[4][5], Interleaving [6], Tone reservation (TR), Tone injection (TI)[8] etc. Are signal scrambling techniques

###### 4.1.1 BLOCK CODING TECHNIQUES

The main objective of this technique is to PAPR using block coding & set of code words. The block coding is widely used for reducing peak to average power ratio. While selection of the codeword many things should be considered like m-ray PSK scheme, coding rate, suitability of encoding-decoding & the main thing is that error correction/decoding. Large PAPR reduction can be achieved by separating the long information sequence into different sub blocks, and all sub blocks encoded on a programmable chip (SOPC).

Partial transmit sequence is the modified technique of SLM technique. It is also based on the probabilistic Theory. The idea of this technique is data block divide into non-overlapping sub blocks, each block having independent rotation factor. This rotation factors generates time domain data having lowest amplitude. This Technique gives better performance than SLM techniques. Because we use differential modulation no need to transmit the side information.

###### 4.1.5 INTERLEAVING

In this technique  $K$  interleaver are used at the transmitter. The output of the interleavers is the  $K$  permuted frames of the input data sequence. This permutation can be generate either before or after the mapping. The frame having minimum PAPR among all the  $K$  frames is selected for transmission, identity of the corresponding interleaver has to be sent to the receiver as the side information [6].

The computer simulation can be seen with  $N=256, 512$  and  $1024$  subcarriers using 16 QAM, 64 QAM. By using this technique highly co-related data structures having large PAPR can be reduced. The main advantages of this technique are that, it is less complex than the PTS scheme but can be obtain comparable result. Although this technique is less complex than PTS, but this method does not give the assurance result for PAPR reduction. also increase the bit error rate which also decreases the spectral efficiency [9].

Filtering technique will give better performance. Filtering after clipping will reduce out of band radiation. Filtering after clipping can reduce the out-of-band expansion. So for proposed this technique each signal must be over sampled by factor of four. This scheme is more suitable with the m-ray PSK modulation scheme.

A  $n$  bit data block is encoded by  $(n, k)$  block code by using the Generator matrix 'G' at the transmitter of the system. The phase rotator vector  $b$  to produce the output of encoder  $x = a.g + b \pmod{2}$ . After the generator matrix 'G' and the phase rotator produced vector 'b'; the encoded data symbol are used modulation. The converse function of the transmitter are perform at the receiver side the parity check matrix 'H' achieve from the generator matrix 'G' the exception is that the phase rotator vector 'b' is removed before syndromes calculation.

##### 4.1.3 SLECTED MAPPING (SLM)

In selected mapping technique the signal contain the same signal but from it most favourable signal is to be chosen. The side information must be added the transmitter with the chosen signal. This technique based on the probability [7]. The probability of PAPR the generated signal larger than a threshold  $Z$  can be written as  $P(\text{PAPR} > Z) = 1 - (1 - \exp(-Z))^N$ . Assuming  $m$  OFDM signal contain the same information and independent each other in this case the probability of PAPR greater than  $Z$  can be written as the product of each independent probability. This can be expressed as  $P\{\text{paprlow} > Z\} = (P\{\text{PAPR} > Z\})^m = ((1 - \exp(-z))^N)^m$  Firstly  $m$  statistically sequences are generated and next the resulting  $m$  statistically independent data blocks  $S_m = [S_m, 0, S_m, 1, \dots, S_m, n-1]T, m=1, 2, \dots, M$

Are than given to the IFFT operation simultaneously. Eventually, the sequences with the smallest PAPR will be selected for final serial transmission. This scheme is very reliable but the drawback is that, side information must be transmitted along with the chosen signal.

##### 4.2.2 PEAK WINDOWING

Peak windowing technique is similar to the clipping technique it gives better performance with adding some self interference and increasing in the bit error rate (BER). Peak windowing reduces PAPRs at the cost of increasing the BER and out-band radiation. In peak windowing method we multiply large signal peak with a specific windowing, for example: Kaiser, cosine, Hamming windowing and Gaussian shaped window [9]. OFDM signal is multiplied with several of these windows; the output of the window is a convolution of the original OFDM spectrum with the spectrum of the applied window. The window should be narrow as possible as. This technique gives PAPR reduction up to 4db of each subcarrier. SNR is limited to 3 db due to signal distortion.

##### 4.2.3 ENVELOPE SCALING

This technique is use scaling means before OFDM signal sent to the IFFT all subcarrier is scaled the input envelope. They used 256 subcarriers with QPSK modulation technique, so that all the subcarriers envelopes are equal.

Main idea of this technique is that the input envelope in some subcarrier is scaled to get the smallest amount of PAPR at the output of the IFFT. Here, there are no needs to transmit any side information for decoding at the receiver. This scheme is suitable for the m-ray PSK modulation. The envelopes of all subcarriers are equal. Results show that PAPR can be reduced significantly at around 4 db. When this scheme uses QAM high degradation is occurred in the BER.

### CONCLUSION

Basically all technique described above to reduced the PAPR in ORDM system are different in their way. Using each technique PAPR can be reduced at some level. To reduce the PAPR any technique can be used.

### REFERENCES

- [1]“[http://telephonyonline.com/wireless/technology/mimo\\_ofdm\\_09](http://telephonyonline.com/wireless/technology/mimo_ofdm_09) 1905.
- [2]V.Kuhn, Bohnke,andK-D.Kammeyer, “Adaptive MIMO –OFDM for future mobile radio communications,” in proceedings of the 6th IEE international conference (GLOBECOM’06), pp.9- 12, London, UK, November 2005
- [3] Bauml, R.W, Fischer, R.F.H and Huber, J.B, “Reducing the peak-to-average power ratio of multicarrier modulation by selected mapping,” IEEE Electronic Letters, vol. 32, no. 22, Oct 1996. 4] T.Jing and Y.Wu, “An overview: Peak-to-Average power ratio reduction of an OFDM,” IEEE Transactions and Broadcasting, vol. 2, no. 5, May 1988, pp.131-133.
- [5] Mountassir jamal , Isar Alexandru “Combined partial transmit sequence and companding for PAPR reduction in OFDM system. ” Proceeding of SPAMEC 2011, Cluj-Napoca,romania.
- [6] H.Y. Sankaran, M.shokair,and A.A. Elazm.” An efficient technique for reducing PAPR of OFDM System in presence of non linear high power amplifier.” Progress in electromagnetic research C, Volume.2, 233-241, 2008.
- [7] X. Li and L.J.Cimini jr.,”Effects of clipping and diltering on the performance on the performance of FDM,” IEEE Common Lett. Vol.2, no.5, May 1988, pp.131-133
- [8] S. H. Muller, J. B. Huber, “A novel peak power reduction scheme for OFDM,” The 8th IEEE International Symposium on Personal, Indoor and Mobile Radio Communications, Feb 1997.
- [9] Arum K. Gureng, Fawaz S. Al-Qastani,.” One iteration clipping filtering (OICF) scheme for PAPR reduction of OFDM signal”.2008 international conference on advanced technologies for communication.

[