

# Maximum Energy Consumption In MANET Using Re-Broadcasting Protocol

Karthika Kothandam<sup>1</sup>, R.Muthuvenkatakrishnan<sup>2</sup>, A.Mani<sup>3</sup>

<sup>1</sup> MTech, Department of CSE, PRIST University,  
Thanjavur, India

<sup>1</sup> [karthirock@gmail.com](mailto:karthirock@gmail.com)

<sup>2,3</sup> Assistant Professor, Department of CSE,  
PRIST University, Thanjavur, India

<sup>2</sup> [muthu.brillia@gmail.com](mailto:muthu.brillia@gmail.com), <sup>3</sup> [inovic.mani@gmail.com](mailto:inovic.mani@gmail.com)

<sup>2</sup>

**Abstract**— In MANET, stable packet transmission plays a virtual role and have best quality of service, frequent change in position of node causes data loss and routing cannot be constant, probability of re-broadcasting cause high redundancy in neighbour coverage and radio signal produce congestion in mac layer and delay the transmission, our Rebroadcasting Neighbour Coverage protocol (RBNC) reduce the congestion and improve the rate of transmission and find best routing to reach destination. Energy efficient routing mechanism is proposed in network with existing routing protocol, it selects the trusted forwarding nodes having higher energy, Maximum energy consumption in network is done by accurate rebroadcasting. Simulating the comparison of routing and energy efficient mechanism in NS2 and the performance is evaluated and rebroadcasting is analytically discussed.

**Keywords**— Rebroadcasting Neighbour Coverage protocol, Mac layer, broadcast, mobile ad hoc network (MANET), Energy.

## I. INTRODUCTION

In Mobile Ad hoc Network (MANET), each node satisfy their service using their own mobility in the network. No centralized and distributed service, user defined service. Here random mobility is the main issue which affect the data delivery, it depends on coverage of neighbors and causes link failure. If network depends on the routing protocol, each and every node works according to the request and response of radio signal broadcasting.

On demand routing protocol works with the basic schema of route selection from source to destination, here delay as to be reduced. Broadcasting is the main problem in MANET (to search neighbour using radio signal with re-broadcasting probability under NCPR protocol. Which explains the covered neighbour and un-covered neighbour (forwarding node selection) in transmission. In this RBNC protocol is proposed which improve the service under congestion control (CRCN mechanism)[1]. In packet transmission channel allocation of mac layer leads to clear transmission in network, without congestion and reduce rebroadcasting probability etc.[1]. Rebroadcasting delay as to be find in order to reduce the probability of broadcasting, repeated selection of neighbour reduce the routing hop delay in transmission, if

neighbour is not selected delay will affect the coverage ratio.[2] Additional coverage ratio of the RREQ packet in transmission calculate the rebroadcast probability in our NCPR protocol [2], it reduce the routing overhead in route discovery, dynamic route discovery affect the mac layer, where packet is split ed according to the channel estimation of packet size and reduce the congestion in transmission.[2]

Gossip based ad hoc routing increase the false adversary message and confuse the routing, here destination find the best and shortest routing in network [3] Change in method as broadcasting like using omni bi directional antenna to cover the radio signal range of 350 meter. [4] extra rebroadcasting causes energy loss in network and affect the node life time. Robust Broadcast Protocol(RBP) provide reliability in broadcasting and communicate with MAC and routing layers. Network density defines the retransmission process and increase the reliability. [5] If a link breakage does not affect packet transmission no global broadcast occurs to find neighbour, AODV reduces the network wide broadcasts to the extent possible of selecting forwarding node in transmission. [6]. Forwarding node selection and rebroadcasting process shows point-to-point communication is replaced with many-to-many cooperative communication, energy efficient routing is defined [7].

Till now we got a survey for rebroadcasting and neighbour coverage protocol, now we are going to discuss that, energy consider network will improve the route discovery efficiently in network and reduce overhead in transmission. EARQ - Energy aware routing provide the reliability in network. It maintain the routing table like proactive routing protocol in manet. [8]. Link utility of routing as to constant. [9] energy dependent routing improve the service in network.

## Main contribution of this paper as follows:

*We propose an Energy consumption RBNC protocol, which improve the quality of service, reduce redundancy and use best energy routing to reach destination.*

Section I explains about the broadcasting, rebroadcasting and finding the covered neighbour with energy, and the issues

discussed with reference etc . And proposed an Energy RBNC protocol improve the quality of service. Section II explains the proposed approach and section III directly show the simulation setup and performance evaluation in IV section.and the result is discussed in rest of the paper.

## II. PROPOSED APPROACH

In this section we are going to discuss about our RBNC protocol and how we add energy to result Energy routing in MANET.




Fig 1: Energy RBNC Routing

### A. RBNC Protocol

Rebroadcasting neighbour coverage protocol (RBNC) reduce the redundant in MAC layer by finding the covered neighbour in transmission.From the figure 1 , we can tell that Source , S node broadcast the radio signal and search the neighbour to select the best forwarding node, S send RREQ to neighbour and which response(RREP) reach Source , select as forwarding node in transmission, again for next route another forwarding node as be select in that source re-broadcast the radio signals and select the best node in the covered neighbour, here n5 is un-covered neighbour , which is not participating in transmission. Cognitive radio congestion network (CRCN) mechanism is used to reduce the redundancy in re-broadcasting and reduce the collision in packet transmission ie., MAC layer , channel assignment and selection process will take place according to the node density and size of the packet.

Here , congestion and redundancy is reduced but efficient forwarding node selection delay the quality of service to improve the ratio of packet delivery.We proposed an Energy RBNC Protocol which satisfy the energy efficient routing in the network.

### B. Energy RBNC Protocol

Energy Efficient Rebroadcasting Neighbour coverage Protocol (Energy RBNC) improve the rate of packet delivery in network by choosing the higher precedence energy level in the forwarding node and allow it in transmission.From the fig 1, we can tell the Source have two neighbour to reach

destination , in this by rebroadcasting find that n2 is the forwarding node but Energy RBNC will select that n2 is having higher precedence or not, if it have then n2 will again reselected for transmission, this process will deliver the data efficiently to destination.

TABLE I  
PERFORMANCE EVALUATIONS

Parameter	AODV	RBNC	E-RBNC
Packet Delivery Ratio ( byts /sec )	690	850	960
End to end Delay (sec)	0.56	0.24	0.198

In other case n5 is selected as forwarding node having less energy and no way to change the routing , surely packet loss will occur , because n5 is not having ability to transmission to destination , here it fails in energy level and randomly showing as un-covered neighbour, as n5(un-covered neighbour- not able to participate in broadcasting as well as in transmission).

### Energy -RBNC Mechanism

```
#define esrbnc_LOCAL_REPAIR
#define esrbnc_LINK_LAYER_DETECTION

for (i in finalenergy) {
    consumenergy[i]=initialenergy-
    finalenergy[i]
    totalenergy +=consumenergy[i]
    if(maxenergy<consumenergy[i]){
        maxenergy=consumenergy[i]
        nodeid=i
    }
}
```

Combining both the RBNC mechanism with the energy estimation of nodes to participate in transmission. Initial energy assumed as 100 Joules and the consumption of energy level is the difference of transmission energy to its initial state. The loss of energy will occur more in re-broadcasting the radio signals , it will be reduced in MAC channel assignment of packet transmission in network.

### C. Energy RBNC in Mac layer

In packet transmission , flooding and unwanted signals , rebroadcasting as to be reduced by channel assignment in MAC layer , It distribute the packet with the scheduling algorithm under MAC distribution in transmission. If MAC channel assignment is not performed in transmission , packet

loss will occur and affect the rebroadcasting in search of neighbour coverage. To avoid those subsequences Mac channel assignment is preceded in Mac layer as Energy RBNC.

### III. SIMULATION SETUP AND PARAMETER

To evaluate the performance of proposed protocol which improve the data delivery rate and reduce the congestion in network. In NS2 simulator, we have simulate the basic routing protocol AODV and congestion and routing protocol RBNC and our proposed approach is evaluated and compared the results to show the improvement in quality of service. Energy is the main role which select the best routing in network without the congestion and link failure to reach destination. Each neighbour with higher energy will be selected as forwarding node. From the Table II, we can tell that, our network scenario is designed with the area of 1000x1000 and randomly 50 nodes are arranged, radio signal range covers 250 meter in the omni directional antenna, node random way point varies up to 30m/sec. Transmission takes with CBR, with minimum packet interval of 1000 bytes, transmission energy starts with 100 joules. Routing protocol is changed with the same scenario and compared the results.

TABLE II  
SIMULATION PARAMETERS

PARAMETER	VALUE
Simulator	Ns2 - 2.31
Number of nodes	50
Simulation Time	15 min
Packet Interval	0.01 sec
Simulation Landscape	1000 x 1000
Background Data Traffic	CBR
Packet Size	1000 bytes
Queue Length	50
Energy	100 Joules
Transmission Range	100 Kbytes
Node Transmission range	250 m
Antenna Type	Omni directional
Mobility Models	Random-waypoint (0-30 m/s)
Radio Frequency	150-350 MHz
Routing Protocol	AODV, RBNC, ES-RBNC
MAC Protocol	IEEE 802.11

#### A. Packet Delivery Ratio

Packet Delivery Ratio is defined as the ratio of packets send and received in the transmission and the unit is byts per sec. From fig 2 we can tell that Energy RBNC is having high delivery ratio when comparing with AODV and RBNC.

#### B. End to End Delay

Time difference between the starting and ending time of transmission in the network is called end to end delay. Fig 3 shows minimum delay in Energy RBNC transmission.

#### C. Energy In Network

Energy consumption in network is defined as the difference between the initial energy to the individual energy (node having energy after the complete the transmission), it is denoted by joules.




Fig 2: Packet Delivery Ratio




Fig 3: Comparison of Delay

### IV. CONCLUSIONS

Thus we have implemented an energy efficient RBNC protocol, which reduce the congestion, redundancy and choose best energy routing in transmission. We improve the quality of service in network and compared with proposed

protocol and solve the MANET issues. Our simulation results show the better achievements in the improvement of Qos. 20 % of service is better than RBNC protocol with Energy Mechanism .

## V. FUTURE ENHANCEMENT

Our Energy RBNC protocol can be verified with the scalability, and location based devices like, GPS, GPSR, WIMAX, and LTE. External energy can be used to improve the lifetime of the node.(batt power) Future enhancement of RBNC protocol mainly concentrate on the radio signal frequency coverage methodology like ellipse, parabola, and by probability distribution with geographic information of the nodes in the network with dynamic topology.




Fig 4: Energy Consumption in Network

## REFERENCES

- [1] Karthika Kothandam, J. Sagaya Rani, and V. Santhana Marichamy, "Rebroadcasting Neighbour Coverage Routing Protocol in MANET using MAC layer Design," International Journal of Computer Applications (0975 – 8887), 2013.
- [2] Xin Ming Zhang, En Bo Wang, Jing Jing Xia, and Dan Keun Sung, "A Neighbour Coverage based Probabilistic Rebroadcast for Reducing Routing Overhead in Mobile Ad hoc Networks" Mobile Computing, IEEE Transactions on VOL. 11, NO. Jan, 2012
- [3] Zygmunt Haas Joseph Y. Halpern Li Li , "Gossip-Based Ad Hoc Routing"
- [4] Wei Peng Xi-Cheng Lu , "On the Reduction of Broadcast Redundancy in Mobile Ad Hoc Networks."
- [5] Fred Stann John, Heidemann Rajesh, Shroff Muhammad, Zaki Murtaza , "RBP: Robust Broadcast Propagation in Wireless Networks"
- [6] Dr. Baruch Awerbuch & Dr. Amitabh Mishra , " Ad hoc On Demand Distance Vector (AODV) Routing Protocol" 2006
- [7] Mohamed Elhawary and Zygmunt J. Haas, "Energy-Efficient Protocol for Cooperative Networks" IEEE/ACM Transactions on networking , April 2011
- [8] Junyoung Heo, Jiman Hong, and Yookun Cho, "EARQ: Energy Aware Routing for Real-Time and Reliable Communication in Wireless Industrial

Sensor Networks ", IEEE Transactions on industrial informatics, 2009

- [9] Issa Khalil and Saurabh Bagchi , Stealthy Attacks in Wireless Ad Hoc Networks: Detection and Countermeasure IEEE Transactions on mobile computing.
- [10] Ns2 Reference from <http://networksimulation.wordpress.com/>
- [11] J. Kim, Q. Zhang, and D. P. Agrawal, "Probabilistic Broadcasting Based on Coverage Area and Neighbour Confirmation in Mobile Ad hoc Networks," Proc. of IEEE GLOBE COM' 04, 2004.
- [12] Y. Sasson, D. Cavin, A. Schiper. Probabilistic Broadcast for Flooding in Wireless Mobile Ad hoc Networks. IEEE Wireless Communications and Networking Conference (WCNC) - March 2003
- [13] Sung-Ju Lee, W. Su, M. Gerla. On-Demand Multicast Routing Protocol (ODMRP) for Ad Hoc Networks. Internet Draft (work in progress), June 1999.
- [14] C. Ho, K. Obraczka, G. Tsodik, and K. Viswanath. Flooding for Reliable Multicast in Multi-Hop Ad Hoc Networks. DIAL M'99, August 1999.
- [15] Nahata, P. Pamu, S. Garg, and A. Helmy. Efficient resource discovery for large scale ad hoc networks using contacts. ACM SIGCOMM Computer Communications Review, 32(3):32, July 2002.

AUTHOR PROFILE :



**Karthika Kothandam** was born in 1985. She received **B.E.** degree from the Department of Electrical and Electronics Engineering, Anna University, Chennai, India, in 2007. She received **MBA** (Human Resource Management) degree from the Department of Management, University of Madras, Chennai, India, in 2011. She is pursuing her **M.Tech** Degree from the Department of Computer Science and Engineering PRIST University, Thanjavur, India. Her fashion is working as a NS2 Developer in **Ambitlick Solutions**. Her research interests are broadcasting RF signals, Congestion Control, Communication in Mobile computing in MANET using Ns2. **Phone: 9884956131**